



**SPECIFICATIONS**

Header Material: Brass, Tin Plated  
 Housing Material: PA66, UL94V-0  
 Voltage Rating: 300V  
 Current Rating: 10A  
 Contact Resistance: 20mΩ  
 Insulation Resistance: 5000MΩ/1000V  
 Withstanding Voltage: AC1500V/1Min.  
 Temp Range: -30C ~ +105C  
 Max Soldering: +250C for 5 Sec.

Series	Type	Pitch	Positions	Color
CMTB	F332N	XXX	XX	XX
Terminal block	F332N Type	500, 508, 1000, 1016	02,03,08, 16	GN=Green BK=Black BL=Blue GY=Gray

RECOMMEND PCB LAYOUT(TOLERANCE=±0.05)

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/04/08
				Checked	Lizzy	08/04/08
				Drawn	Tina	08/04/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F332N-500-XX-XX**

Description: Euro Terminal Blocks Pitch 5.0mm