



**SPECIFICATIONS**

- Voltage Rating: 300V
- Current Rating: 15A
- Contact Resistance: 20mΩ
- Insulation Resistance: 5000MΩ/1000V
- Contact: Phosphor Bronze
- Screws: M2.5 Steel Zinc Plated
- Housing: PA66, UL94V-0
- Withstanding: AC1500V/1 Min
- Max Soldering: +250C for 5 Sec.
- Torque: 0.5Nm (4.5Lb/In)
- Tempe Range: -40C to +105C

Series	Type	Pitch	Positions	Color
CMTB	F515HA	XXX	XX	GN
Terminal Block	Wire Mount Type A	500=5.00mm 508=5.08mm 1000=10.00mm 1016=10.16mm	500/508: 02-24 1000/1016: 02-12	GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/16/10
				Checked	Lizzy	08/16/10
				Drawn	Tina	08/16/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F515HA-1000-XX-GN**

Description: Terminal Block