



SPECIFICATIONS

- Current Rating: 16Amp AC300V
- Contact Material: Phosphor Bronze, Tin Plated
- Insulation Material: Polyamide 66 UL94V-0
- Insulation Resistance: 5000MΩ min
- Clamp Material: Brass, Nickel Plated
- Screw Material: Steel, Zinc Plated
- Wire Strip Length: 7-8mm
- Wire Range: 28-12AWG
- Screw Torque: 4.5 Lb-inch
- Withstanding: AC 1500V min
- Operating Temp: -40°C to +105°C

Series	Type	Pitch	Positions	Color
CMTB	FMC200	XXX	XX	XX
Terminal block	Wire mount type	750=7.5mm 762=7.62mm	2-24	GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/08/07
				Checked	Lizzy	07/08/07
				Drawn	Tina	07/08/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-FMC200-XXX-XX-GN**

Description: Terminal Block, Wire Mount Type