



**SPECIFICATIONS**

Current rating: 10 amps  
 Operating voltage: 300VAC  
 Terminal material: Brass  
 Terminal plating: Tin  
 Screw material: Steel  
 Screw plating: Nickel  
 Barrier material: Thermoplastic, UL94V-0, black  
 Insulator resistance: 500 megohms min.  
 Withstanding: 200VAC  
 Wire Range: AWG 18 to AWG 22, stranded

Series	Type	Pitch	Poles	Color
CMTB	FTB702XX	762	XX	BK
Terminal block	[blank]=No options C=Cover F=Flange	762=7.62mm pitch	02-32 poles	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		


**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-FTB702XX-762-XX-BK**

Description: 7.62mm pitch barrier strip, style 2