



SPECIFICATIONS

Housing Material: Polyamide 66 UL94V-2, Black
 Insulation Resistance: >1000MΩ at DC500V
 Screw: M3.0 Nickel Plated Steel
 Terminals: Tin Plated Brass
 Cover: PC Transparent
 Screw Torque: 7 in-Lb
 Wire Range: 16~22 AWG
 Rated: 10 Amperes AC250V
 Operating Temp: -55C ~ +100C
 Withstanding: AC 2000V min

Dimensions					
Pole	A	B	Pole	A	B
2	16.94	7.62	18	138.86	129.54
3	24.56	15.24	19	146.48	137.16
4	32.18	22.86	20	154.1	144.78
5	39.8	30.48	21	161.72	152.4
6	47.42	38.1	22	169.34	160.02
7	55.04	45.72	23	176.96	167.64
8	62.66	53.34	24	184.58	175.26
9	70.28	60.96	25	192.2	182.88
10	77.9	68.58	26	199.82	190.5
11	85.52	76.2	27	207.44	198.12
12	93.14	83.82	28	215.06	205.74
13	100.76	91.44	29	222.68	213.36
14	108.38	99.06	30	230.30	220.98
15	116	106.68	31	237.92	228.60
16	123.62	114.3	32	245.54	236.22
17	131.14	121.92			

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/15/05
				Checked	Lizzy	10/15/05
				Drawn	Tina	10/15/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-FTB706X-762-XX-BK**

Description: Barrier Type Terminal Block