



SPECIFICATIONS

Current rating: 10 amps
 Operating voltage: 300VAC
 Terminal material: Brass
 Terminal plating: Tin
 Screw material: Steel
 Screw plating: Nickel
 Barrier material: Thermoplastic, UL94V-0, black
 Insulator resistance: 500 megohms min.
 Withstanding: 2,000VAC
 Wire Range: AWG 18 to AWG 22, stranded

Series	Type	Pitch	Poles	Color
CMTB	FTB706XX	762	XX	BK
Terminal block	[blank]=No options C=Cover F=Flange	762=7.62mm pitch	02-32 poles	BK=Black
			FC=Flange & cover	

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-FTB706XX-762-XX-BK**

Description: 7.62mm pitch barrier strip, style 6