



**SPECIFICATIONS**

- Voltage Rating: AC 250V
- Withstanding: AC2000V min
- Insulation Resistance: > 1000MΩ or more at DC500V
- Screw Torque: 8 in-lb
- Wire Range: 16~22 AWG
- 1. Housing Materials: Polyamide 66UL94V-0 Black
- 2. Screw: M3.0 Nickel Plated Steel
- 3. Terminals: Tin Plated Brass
- 4. Cover: PC Transparent
- Operating Temp: -55C ~ +95C

Dimensions mm					
Item	A	B	Item	A	B
2	35.00	24.75	17	158.75	148.50
3	43.25	33.00	18	167.00	156.75
4	51.50	51.25	19	175.25	165.00
5	59.75	49.50	20	183.50	173.25
6	68.00	57.75	21	191.75	181.50
7	76.25	66.00	22	200.00	189.75
8	84.50	74.25	23	208.25	198.00
9	92.75	82.50	24	216.50	206.25
10	101.00	90.75	25	224.75	214.50
11	109.25	99.00	26	233.00	222.75
12	117.50	107.25	27	241.25	231.00
13	125.75	115.50	28	249.50	239.25
14	134.00	123.75	29	257.80	247.50
15	142.25	132.00	30	266.00	255.80
16	150.20	140.25			

Other pin styles available

Series	Type	Pitch	Poles	Color
CMTB	FTB802XX	825	XX	BK
Terminal block	XX: [blank]=No options F=Flange	C=Cover FC=Flange & cover	825=8.25mm pitch	02-30 poles
				BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	8/10/99
				Checked	Lizzy	8/10/99
				Drawn	Tina	8/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-FTB802FC-825-XX-BK**

Description: 8.25mm pitch barrier strip