



SPECIFICATIONS

- Voltage Rating: 300V
- Current Rating: 8A
- Contact Pin: Brass
- Wire Guard: Stainless Steel
- Solder Tail: Tin Plated
- Insulation Material: Thermoplastic UL94V-0
- Solid Wire: 16-20 AWG
- Stranded Wire: 16-20 AWG
- Wire Strip Length: 9~10mm
- Withstanding: 1.6KV
- Operating Temp: 30°C to +105°C

Series	Type	Pitch	Positions	Color
CMTB	H7M	XXX	XX	XX
Terminal Block	Single Position Modular	500=5.00mm 750=7.50mm	02-24	GN=Green BK=Black GY=Gray (Other colors available. Colors can be mixed.)

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/20/05
				Checked	Lizzy	12/20/05
				Drawn	Tina	12/20/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-H7M-500-06-XX**

Description: Terminal Block 5.0mm pitch