



SPECIFICATIONS

Housing Material: PA 66 UL94V-0 Black
 Screw: M3.5 Nickel Plated Steel
 Terminals: Tin Plated Brass
 Cover: PC Transparent
 Screw Torque: 15.7 In-Lb
 Wire Range: 12~22 AWG
 Rated: 25 Amperes AC300V
 Operating Temp: -55C ~ +105C
 Withstanding: AC 200V min
 Insulation Resistance: >1000MΩ or more @ DC500V

Dimensions					
Poles	A	B	Poles	A	B
2	20.4	9.50	15	143.9	133.0
3	29.9	19.0	16	153.4	142.5
4	39.4	28.5	17	162.9	152.0
5	48.9	38.0	18	172.4	161.5
6	58.4	47.5	19	181.9	171.0
7	67.9	57.0	20	191.4	180.5
8	77.4	66.5	21	200.9	190.0
9	86.9	76.0	22	210.4	199.5
10	96.4	85.5	23	219.9	209.0
11	105.9	95.0	24	229.4	218.5
12	115.4	104.5	25	238.9	228.0
13	124.9	114.0	26	248.4	237.5
14	134.4	123.5	27	257.9	247.0

Series	Type	Pitch	Positions	Color
CMTB	HD122X	950	XX	BK
Terminal Block	Barrier Strip, R/A X; C=With Cover [blank] = No Cover	950=9.5mm	02-27	Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/06/11
				Checked	Lizzy	12/06/11
				Drawn	Tina	12/06/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: in		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-HD122X-950-XX-BK**

Description: Barrier Type Terminal Block