



SPECIFICATIONS

Housing Material: PA 66 UL94V-0, Black
 Screw: M3.5 Nickel Plated Steel
 Terminals: Tin Plated Brass
 Cover: PC Transparent
 Screw Torque: 15.7 in-lb
 Wire Range: 12~22 AWG
 Rated: 25 Amperes AC300V
 Operating Temp: -55C ~ 105C
 Withstanding: AC2000V min
 Insulation Resistance: >1000MΩ or more @ DC500V

Dimensions					
Poles	A	B	Poles	A	B
2	20.4	9.5	15	143.9	133
3	29.9	19	16	153.4	145.5
4	39.4	28.5	17	162.9	152
5	48.9	38	18	172.4	161.5
6	58.4	47.5	19	181.9	171
7	67.9	57	20	191.4	180.5
8	77.4	66.5	21	200.9	190
9	86.9	76	22	210.4	199.5
10	96.4	85.5	23	219.9	209
11	105.9	95	24	229.4	218.5
12	115.4	104.5	25	238.9	228
13	124.9	114	26	248.4	237.5
14	134.4	123.5	27	257.9	247

Series	Type	Pitch	Positions	Color
CMTB	HD124X	950	XX	BK
Terminal Block	Straight offset pin X: C=w/ cover (19 pins) Blank=no cover	950=9.5mm	02-27	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/09/06
				Checked	Lizzy	08/09/06
				Drawn	Tina	08/09/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-HD124X-950-XX-BK**

Description: Barrier Strip, Straight PCB Mount