



SPECIFICATIONS

Housing Material: PBT UI94V-0, Black
 Insulation Resistance: >1000MΩ or more at DC 500V
 Screw: M4.0 Nickel Plated Steel
 Terminals: Tin Plated Brass
 Cover: PC Transparent
 Screw Torque: 15.7 in-lb
 Wire Range: 10~18 AWG
 Rated: 35 Amperes AC300V
 Operating Temp: -55C ~ +105C
 Withstanding: AC 2000V min

Dimensions					
Pole	A	B	Pole	A	B
2	24	11	14	156	143
3	35	22	15	167	154
4	46	33	16	178	165
5	57	44	17	189	176
6	68	55	18	200	187
7	79	66	19	211	198
8	90	77	20	222	209
9	101	88	21	233	220
10	112	99	22	244	255
11	123	110	23	255	242
12	134	145			
13	145	132			

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/15/05
				Checked	Lizzy	10/15/05
				Drawn	Tina	10/15/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-HD141X-1100-XX-BK**

Description: Barrier Type Terminal Block