



**SPECIFICATIONS**

Current rating: 11 amps  
 Voltage rating: 250VAC  
 Terminal material: Brass  
 Terminal plating: Tin  
 Wire protector material: Brass  
 Wire protector plating: Tin  
 Housing material: Polyamide 66, UL94V-0, green  
 Lever material: Polyamide 66, UL94V-0, orange  
 Insulation resistance: 1,000 megohms min. at 500VDC  
 Withstanding: 2,000VAC for 1 min.



Series	Type	Pitch	Positions	Color
CMTB	HD522	XXX	XX	XX
Terminal block	Screwless type	500=5.00mm 508=5.08mm (.200")	2-24	GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-HD522-500-XX-XX**

Description: Terminal block, screwless, 5.00mm pitch