



Pole	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
A	13.85	20.2	26.55	32.9	39.25	45.6	51.95	58.3	64.65	71.0	77.35	83.7	90.05	96.4	102.75	109.1
B	6.35	12.7	19.05	25.4	31.75	38.1	44.45	50.8	57.15	63.5	69.85	76.2	82.55	88.9	92.25	101.6
Pole	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	
A	115.45	121.8	128.15	134.5	140.85	147.2	153.55	159.9	166.25	172.6	179.0	185.3	191.7	198.0	204.35	
B	107.95	114.3	120.65	127.0	133.35	139.7	146.05	152.4	158.75	165.1	171.5	177.8	184.2	190.5	196.90	

SPECIFICATIONS

Voltage rating: 250VAC
 Current rating: 10 amps
 Withstanding: 2000VAC
 Insulation resistance: 500VDC
 Barrier material: Thermoplastic, UL94V-0, black
 Terminal material: Brass
 Terminal plating: Tin
 Screw material: Steel
 Screw plating: Nickel
 Wire range: AWG18-22, stranded

Series	Type	Pitch	Poles	Color
CMTB	HD60XX	635	XX	BK
Terminal block	1=No flange 2=Flange C=Optional cover	6.35mm	02-32	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-HD601C-635-XX-BK**

Description: Barrier strip terminal block, 6.35mm pitch, no flange, optional cover