



SPECIFICATIONS

Screws Torque: 7 In-Lb
 Wire Range: 16~22 AWG
 Rating: 15 Amperes AC250V
 Insulation Resistance: >1000Ω
 Withstanding: AC 2000V
 Operating Temp: -55C ~ +95C

Dimensions					
Pole	A	B	Pole	A	B
2	20.04	7.62	16	126.72	114.3
3	27.66	15.24	17	134.34	121.92
4	35.28	22.86	18	141.96	129.54
5	42.9	30.48	19	149.58	137.16
6	50.52	38.1	20	157.2	144.78
7	58.14	45.72	21	164.82	152.4
8	65.78	53.34	22	172.44	160.02
9	73.38	60.96	23	180.06	167.64
10	81	68.58	24	187.68	175.26
11	88.62	76.2	25	195.3	182.88
12	96.24	83.82	26	202.92	190.5
13	103.86	91.44	27	210.54	198.12
14	111.48	99.06	28	218.16	205.74
15	119.1	106.68	29	225.78	213.36
			30	233.4	220.98
			31	241.02	228.6
			32	248.64	236.22

Item	Name	Material	Finish
1	Housing	Polyamide66 UL94V-0	Black
2	Screw	M3.5	Nickel Plated Steel
3	Terminals	Brass	Tin Plated

Series	Type	Pitch	Positions	Color
CMTB	HD741	762	XX	BK
Terminal block	Screwless type	762=7.62mm	2-32	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-HD741-762-XX-BK**

Description: Double Row Type Terminal Block

