



SPECIFICATIONS

Housing Material: Polyamide 66(UL94V-0) Black
 Screw: M 3.0 Nickel Plated Steel
 Terminals: Tin Plated Brass
 Screw Torque: 7 in-lb
 Wire Range: 14~18 AWG
 Rated: 20 Amp AC 300V
 Operating Temp: -55C ~ +95C
 Withstanding: AC 2000V min
 Insulation Resistance: > 1000MΩ or more at DC 500V

Dimensions					
Pole	A	B	Pole	A	B
4	18.50	8.25	34	142.25	132.00
6	26.75	16.50	36	150.50	140.25
8	35.00	24.75	38	158.75	148.50
10	43.25	33.00	40	167.00	156.75
12	51.5	41.25	42	175.25	165.00
14	59.75	49.50	44	183.50	173.25
16	68.00	57.75	46	191.75	181.50
18	76.25	66.00	48	200.00	189.75
20	84.50	74.25	50	208.25	198.00
22	92.75	82.50	52	216.50	206.25
24	101.00	90.75	54	224.75	214.50
26	109.25	99.00	56	233.00	222.75
28	117.50	107.25	58	241.25	231.00
30	125.75	115.50	60	249.50	239.25
32	134.00	123.75			

Series	Type	Pitch	Positions	Color
CMTB	HD841	XXX	XX	BK
Terminal block	PCB Mount	825=8.25mm	4-60	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/06
				Checked	Lizzy	05/15/06
				Drawn	Tina	05/15/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-HD841-825-XX-BK**

Description: Dual Level PCB Type Terminal Block