



**SPECIFICATIONS**

Housing Material: Polyamide 66 UL94V-0 Black  
 Screw: M3.5 Nickel Plated Steel  
 Terminals: Tin Plated Brass  
 Cover: PC Transparent  
 Screws Torque: 12 in-lb  
 Wire Range: 14~22 AWG  
 Rated: 10 Amperes AC250V  
 Operating Temp: -55C ~ 95C  
 Withstanding: AC2000V min  
 Insulation Resistance: >1000MΩ or more at DC500V

Dimensions					
Poles	A	B	Poles	A	B
2	21.1	9.5	18	173.1	161.5
3	30.6	21.1	19	182.6	171
4	40.1	28.5	20	192.1	180.5
5	49.6	38	21	201.6	190
6	59.1	47.5	22	211.1	199.5
7	68.6	57	23	220.6	209
8	78.1	66.5	24	230.1	218.5
9	87.6	76	25	239.6	228
10	97.1	85.5	26	249.1	237.5
11	106.6	95	27	258.6	247
12	116.1	104.5	28	268.1	256.5
13	125.6	114	29	277.6	266
14	135.1	123.5	30	287.1	275.5
15	114.6	133	31	296.6	285
16	154.1	142.5	32	306.1	294.5
17	163.6	152			

Series	Type	Pitch	Positions	Color
CMTB	HI204X	950	XX	BK
Terminal Block	Straight offset pin X: C=w/cover (19 pos max) Blank=no cover	950=9.5mm	02-27	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/09/06
				Checked	Lizzy	08/09/06
				Drawn	Tina	08/09/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-HI204X-950-XX-BK**

Description: Barrier Strip, Straight PCB Mount