



**SPECIFICATIONS**

- Current rating: 16 amps at 250VAC
- Terminal material: Brass
- Terminal plating: Tin
- Body material: Polyester
- Insulation resistance: 5,000 megohms min. at 500VDC
- Wire protector: Stainless strip steel
- Screw material: M3.0 steel
- Screw plating: Nickel
- Screw torque: 4.0 lb-inch
- Color: Blue
- Withstanding: 1,500VAC min.
- Operation temperature: -33°C to 105°C
- Short-time temperature: up to 250°C ( 482°C)
- PCB hole diameter: ø1.4mm
- Wire strip length: 4 ~ 5mm
- Wire range: 14 ~ 22 AWG

Series	Positions	Body Style	Color
CMTB	X	MA522M	XX
Terminal block	2-3	Mini terminal block	BL=Blue GY=Gray GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		


**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MA522M-XX-XX**

Description: Mini PCB terminal block