







# PCB Layout



## SPECIFICATIONS

Current Rating: 10 Amp AC300V  
 Insulation Resistance: 2000MQ min  
 Withstanding: AC 2000V min  
 Operating Temp: -40°C to +105°C

Dimensions mm			
Poles	A	Poles	A
2	10.00	15	75.00
3	15.00	16	80.00
4	20.00	17	85.00
5	25.00	18	90.00
6	30.00	19	95.00
7	35.00	20	100.00
8	40.00	21	105.00
9	45.00	22	110.00
10	50.00	23	115.00
11	55.00	24	120.00
12	60.00	25	125.00
13	65.00		
14	70.00		

RoHS compliant

Item	Name	Material	Finish
1	Insulating Body	Polyamide 66(UL94V-0)	Grey
2	Terminal	Brass	Tin Plated
3	Cage Clamp	Steel	Ni Plated
4	Screw	Steel	Zinc +Cr <sup>+3</sup>

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/22/06
				Checked	Lizzy	02/22/06
				Drawn	Tina	02/22/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MB220M-500-XX-GN**

Description: Modular Terminal Block, 5.00mm Pitch