



SPECIFICATIONS

Current rating: 16 amps
 Contact material: Brass
 Contact plating: 0.8T tin
 Insulation material: Polyamide66, UL94V-0
 Insulation resist.: 5,000 megohms min.
 Withstanding: 2,000VAC for 1 min.
 Cage clamp material: Brass
 Cage clamp plating: Nickel
 Screw material: M2.6 steel
 Screw plating: Nickel
 Wire strip length: 4~5mm
 Wire range: 14-24AWG
 Screw torque: 5.0 lb-inch
 Operating temperature: -50°C to +105°C
 Short-time temperature: Up to 250°C (+482°F)

| Series | Type | Pitch | Positions | Color |
|----------------|--|--|-----------|----------|
| CMTB | MB322M | XXX | XX | GN |
| Terminal block | Modular 35° wire entry, 2 and 3 positions (available as single mold in 5mm pitch) | 500=5.00mm pitch 508=5.08mm pitch 750=7.50mm pitch 762=7.62mm pitch | 02-24 | GN=Green |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | | UNIT: mm | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MB322M-508-XX-GN**

Description: Terminal block, modular, 35° wire entry