



SPECIFICATIONS

- Current rating: 16 amps
- Contact material: Brass
- Contact plating: 0.8T tin
- Insulation material: Polyamide66, UL94V-0
- Insulation resistance: 5,000 megohms min.
- Withstanding: 2,000VAC for 1 min.
- Cage clamp material: Brass
- Cage clamp plating: Nickel
- Screw material: M2.6 steel
- Screw plating: Nickel
- Wire strip length: 4~5mm
- Wire range: 14-24AWG
- Screw torque: 5.0 lb-inch
- Operating temperature: -50°C to +105°C
- Short-time temperature: up to 250°C (+482°F)

RoHS compliant

Series	Type	Pitch	Positions	Color
CMTB	MB322M	XXX	XX	GN
Terminal block	Modular 35° wire entry, 2 and 3 positions (available single mold in 5mm pitch)	500=5.00mm pitch 508=5.08mm pitch 750=7.50mm pitch 762=7.62mm pitch	02-24	GN=Green

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MB322M-762-XX-GN**

Description: Terminal block, modular, 35° wire entry