



**SPECIFICATIONS**  
 Current rating: 16 amps  
 Voltage rating: 300 VAC  
 Insulation resistance: 2,000 megohms min.  
 Operating temperature: -40°C to +105°C  
 Wire range: 14-26 AWG  
 Screw torque: 4.5 lb-in

Item	Name	Material	Finish
1	Insulator	Polyamide 66 UL94V-0	Green
2	Terminal	Brass	Tin
3	Screw	Steel	Chrome
4	Cage clamp	Brass	Nickel

Dimensions		
Poles	A(mm)	B(mm)
4	12.70	5.08
6	17.78	10.16
8	22.86	15.24
10	27.94	20.32
12	33.02	25.40
14	38.10	30.48
16	43.18	35.56
18	48.26	40.64
20	53.34	45.72
22	58.42	50.80
24	63.50	55.88
26	68.58	60.96
28	73.66	66.04
30	78.74	71.12
32	83.82	76.20

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99

0.0 ± 0.35    0.00 ± 0.20    Angles ± 3°  
 UNIT: mm

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MB642-508A-XX-GN**

Description: Stacked terminal block, 5.08mm pitch, side entry top screw