



SPECIFICATIONS

Current Rating: 30Amp AC300v
 Insulation Resistance: 2000MΩ min. at DC500V
 Insulation Withstanding: AC2000V min
 Wire Strip Length: 8mm
 Wire Range: 10-20 AWG
 Screw Torque: 5.5 lb-inch
 Operating Temp: -40°C to +105°C

Dimensions			
Poles	A (in)	Poles	A (in)
2	12.70 (.50)	15	95.25 (3.75)
3	19.05 (.75)	16	101.60 (4.00)
4	25.40 (1.00)	17	107.95 (4.25)
5	31.75 (1.25)	18	114.30 (4.50)
6	38.10 (1.50)	19	120.65 (4.75)
7	44.45 (1.75)	20	127.00 (5.00)
8	50.80 (2.00)	21	133.35 (5.25)
9	57.15 (2.25)	22	139.70 (5.50)
10	63.50 (2.50)	23	146.05 (5.75)
11	69.85 (2.75)	24	152.40 (6.00)
12	76.20 (3.00)	25	158.75 (6.25)
13	82.55 (3.25)		
14	88.90 (3.50)		

RoHS compliant

Item	Name	Material	Finish
1	Insulating Body	Polyamide 66 (UL94V-0)	Green
2	Cage Clamp	Steel	Nickel Plated
3	Terminal	Brass	Tin Plated
4	Screw	Steel	Nickel Plated

Series	Type	Pitch	Positions	Color
CMTB	MB910M	XXX	XX	GN
Terminal Block	Type MB910, Vertical, Modular available in R/A	762=7.62mm 635=6.35mm 952=9.52mm	02-25	GN=Green

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	01/20/09
				Checked	Lizzy	01/20/09
				Drawn	Tina	01/20/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MB910M-635-XX-GN**

Description: Terminal Block, MB910 Type, virtual

