



Pitch: 5.08mm (0.200")					
Poles	A(mm)	B(in)	Poles	A(mm)	B(in)
2	20.32	0.800	14	81.28	3.200
3	25.40	1.000	15	86.36	3.400
4	30.48	1.200	16	91.44	3.600
5	35.56	1.400	17	96.52	3.800
6	40.64	1.600	18	101.60	4.000
7	45.72	1.800	19	106.68	4.200
8	50.80	2.000	20	111.76	4.400
9	55.88	2.200	21	116.84	4.600
10	60.96	2.400	22	121.92	4.800
11	66.04	2.600	23	127.00	5.000
12	71.12	2.800	24	132.08	5.200
13	76.20	3.000			

SPECIFICATIONS
 Current rating: 16 amps
 Contact material: Phosphor bronze
 Contact plating: Tin
 Insulation material: Polyamide66, UL94V-0
 Insulation resist.: 5,000 megohms min.
 Withstanding: 2,000VAC for 1 min.
 Screw material: M2.6 steel, chromated
 Wire strip length: 10mm
 Wire range: 14-24AWG
 Operating temperature: -50°C to +105°C

Series	Type	Pitch	Positions	Color
CMTB	MC311	XXX	XX	GN
Terminal block	Plug, top entry	500=5.00mm pitch 508=5.08mm pitch	02-24	GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MC311-XXX-XX-GN**

Description: Terminal block, plug, top screw, top wire entry, with flanges