



SPECIFICATIONS

Current Rating: 15A
 Voltage Rating: AC 300V
 Wire Protector: Phosphor bronze, tin plated
 Cage Clamp: Steel, Nickel plated
 Housing Material: Polyamide66 (UL94V-0)
 Wire Size: 24~16AWG
 Screw Size: M2.6, steel, Zinc plated
 Torque: 3.0 lb-inch
 Insulation Resistance: >2000MΩ DC500V
 Withstanding: AC1500V min
 Operating Temp.: -40°C to +105°C

Pitch 5.00mm (0.197 inch)		
Poles	A(mm)	B(inch)
2	10.00	0.394
3	15.00	0.591
4	20.00	0.787
5	25.00	0.984
6	30.00	1.181

Item	Name	Material	Finish
1	Insulating Body	Polyamide 66(UL94V-0)	Black
2	Contact	Phosphor Bronze	Tin Plated
3	Cage Clamp	Steel	Nickel Plated
4	Screw	Steel	Zinc +Cr +3

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/28/08
				Checked	Lizzy	04/28/08
				Drawn	Tina	04/28/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MD110-500- XX-BK**

Description: Terminal Block MD type