



SPECIFICATIONS

- Current rating: 12 amps
- Voltage rating: 300VAC
- Solder pin: 1mm brass, tin plated
- Body material: Polyamide66; UL94V-0
- Insulation resistance: 5,000megohm min. at 500VDC
- Withstanding: 2,000VAC min.
- Operating temperature: -55°C to +105°C

RoHS compliant

| Series | Style | Pitch | Positions | Color |
|----------------|-------------------------------|------------|-----------|----------|
| CMTB | ME040 | XXX | XX | GN |
| Terminal block | Vertical closed end plug-able | 381=3.81mm | 02-24 | GN=Green |
| | | 500=5mm | | |
| | | 508=5.08mm | | |
| | | 762=7.62mm | | |

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------------|-------------|-------------|--------|----------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' | | |
| | | | | UNIT: mm | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-ME040-508-XX-GN**

Description: Terminal block, vertical, closed end, plug-able