



SPECIFICATIONS

Housing Material: Polyamide 66 UL94V-0 Black
 Screw: M2.6 Nickel Plated Steel
 Terminals: Tin Plated Brass
 Screw Torque: 3 in Lb
 Wire Range: 14-24 AWG
 Rated: 12 Amperes AC300V
 Operation Temp: -55C ~ +115C
 Insulation Withstanding: AC 2000V min
 Insulation Resistance: > 1000MΩ min. at DC500V

Dimensions		
Poles	A	B
2	10.3	5.0
3	15.3	15.3
4	20.3	15.0
5	25.3	20.0
6	30.3	25.0
7	35.3	30.0
8	40.3	35.0
9	45.3	40.0
10	50.3	45.0
11	55.3	50.0
12	60.0	55.0
13	65.3	60.0
14	70.3	65.0
15	75.3	70.0
16	80.3	75.0
17	85.3	80.0
18	90.3	85.0
19	95.3	90.0
20	100.3	95.0
21	105.3	100.0
22	110.3	105.0
23	115.3	110.0
24	120.3	115.0
25	125.3	120.0



Series	Type	Pitch	Positions	Color
CMTB	MHD90H	500	XX	BK
Terminal block	Modular PCB pin mount, top screw side entry	500=5.00mm	02-25	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/15/00
				Checked	Lizzy	11/15/00
				Drawn	Tina	11/15/00
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MHD90H-500-XX-BK**

Description: PCB Type Terminal Block