


**SPECIFICATIONS**

Voltage Rating: 300V  
 Current Rating: 16A  
 Contact Res.: 20mΩ  
 Insulation Res.: 5000MΩ/1000V  
 Withstanding: 1500 VAC/1 min.  
 Housing: PA99, UL94V-0  
 Contacts: Brass  
 Pins: Brass Tin Plated  
 Screws: M2.5, Zinc Plated  
 Torque: 3.6lb/in  
 Operating Temp.: -40°C to +105°C  
 Processing Temp.: +250°C/5 Sec. Max

Wire Range: 22-12AWG  
 Strip Length: 4.5 to 5mm

**P.C.B. LAYOUT**



Series	Type	Pitch	Positions	Color
CMTB	MK330	XXX	XX	XX
Terminal block	45° entry modular	500=5.00mm 1000=10.00mm	02,03	GN=Green BK=Black BL=Blue GY=Gray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/10/02
				Checked	Lizzy	03/10/02
				Drawn	Tina	03/10/02
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-MK330-500-02-XX**  
 Description: Modular terminal block, 45° entry, through hole PCB mount