



Dimensions & Specifications

Model	Cross Sec.	AWG	Screw	A	B	C	D	E	F	Approvals	Ratings	UL Rating
CMTB-PA8	1.5mm	#22-#12 Sol/Str	M2.6x5	96.20	17.00	14.50	8.20	2.90	2.8±0.1		450V, 17.5A	300V, 20A, #22-#12
CMTB-PA10	2.5mm	#22-#12 Sol #14-#10 Str	M3.0x6	117.2	20.20	16.80	10.00	3.60	3.4±0.1		450V, 24A	300V, 30A, #20-#10
CMTB-PA12	6mm	#22-#10 Sol/Str	M3.5x7	140.7	23.80	19.00	12.00	3.90	4.2±0.1		500V, 41A	300V, 35A, #22-#10
CMTB-PA14	10mm	#20-#8 Sol/Str	M4.0x9	158.0	25.60	25.00	13.50	4.40	5.0±0.1		500V, 57A	300V, 50A, #20-#8
CMTB-PA16	16mm	#14-#6 Sol/Str	M4.0x9	170.0	28.10	23.00	14.50	4.20	6.0±0.1		500V, 76A	300V, 68A, #14-#16

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-PAXX**

Description: Terminal Block, Raised Base Type