



Pitch: 8.25mm (0.33 in.)		
Poles	L(mm)	S(mm)
2	18.2	8.25
3	26.4	16.5
4	34.7	24.8
5	42.9	33.0
6	51.2	41.3
7	59.4	49.5
8	67.7	57.8
9	75.9	66.0
10	84.2	74.3
11	92.5	82.5
12	100.7	90.8
13	109.0	99.0
14	117.2	107.0
15	125.5	116.0
16	133.7	124.0
17	142.0	132.0
18	150.2	140.0
19	158.5	149.0
20	166.7	157.0
21	175.0	165.0
22	183.2	173.0
23	191.5	182.0
24	199.7	190.0
25	208.0	198.0
26	216.2	206.0
27	224.5	215.0
28	232.7	223.0
29	241.0	231.0
30	249.2	239.0

SPECIFICATIONS
 Current rating: 10 amps at 300VAC
 Withstanding: 200VAC min.
 Insulation resistance: 2,000 megohms at 500VAC min.
 Operating temperature: -40°C to +120°C

Item	Name	Material	Finish
1	Insulating body	PBT(UL94V-0)	Black
2	Terminal	Brass	Tin plated
3	Screw	Steel	Nickel plated

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles $\pm 3'$
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-T32BW12-825-XX-BK**

Description: Barrier strip, right angle, thru-hole, 8.25mm pitch