



SPECIFICATIONS

Current Rating: 20 Amp AC300V
 Withstanding: AC2000V min
 Insulation Resistance: >2000MΩ DC500V
 Wire Range: 14~22 AWG
 Screw Torque: 12 lb-inch
 Operating Temp: -40C to 120C

Dimensions					
Poles	A	B	Poles	A	B
2	21.50	9.50	15	145.00	133.00
3	31.00	19.00	16	154.50	142.50
4	40.50	28.50	17	164.00	152.00
5	50.00	38.00	18	173.50	161.50
6	59.50	47.50	19	183.00	171.00
7	69.00	57.00	20	192.50	180.50
8	78.50	66.50	21	202.00	190.00
9	88.00	76.00	22	211.50	199.50
10	97.50	85.50	23	221.00	209.00
11	107.00	95.00	24	230.50	218.50
12	116.50	104.50	25	240.00	228.00
13	126.00	114.00			
14	135.50	123.50			

Item	Name	Material	Finish
1	Insulating Body	PBT UI94V-0	Black
2	Terminal	Brass	Tin Plated
3	Screw	Steel	Ni Plated
4	Cover	PC	

Series	Type	Pitch	Positions	Color
CMTB	T34ES11X	950	XX	BK
Terminal Block	Straight offset pin X:C=w/ cover (19 pos) Blank=no cover	950=9.5mm	02-25	BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/09/06
				Checked	Lizzy	08/09/06
				Drawn	Tina	08/09/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-T34ES11X-950-XX-BK**

Description: Barrier Strip, Straight PCB Mount