



SPECIFICATIONS
 Current Rating: 25Amp AC300V
 Insulation Resistance: >2000MΩ DC500V
 Withstanding: AC2000V min
 Operating Temp: -40C to +120C

OTHER TAIL CONFIGURATIONS
 AVAILABLE

Dimensions		
Poles	L	S
02	24.4	11.0
03	35.4	22.0
04	46.4	33.0
05	57.4	44.0
06	68.4	55.0
07	79.4	66.0
08	90.4	77.0
09	110	88.0
10	112	99.0
11	123	110
12	134	121
13	145	132
14	156	143
15	167	154
30	332	319

Item	Name	Material	Finish
1	Insulating Body	PBT (UL94V-0)	Black
2	Terminal	Brass	Tin Plated
3	Screw	Steel	Ni Plated

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/30/02
				Checked	Lizzy	07/30/02
				Drawn	Tina	07/30/02
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-T36M61-1100-XX-BK**

Description: Terminal Block