



**SPECIFICATIONS**

Current Rating: 40Amp AC600V  
 Insulation Resistance: >2000MΩ DC500V  
 PCB Hole Dia: ø2.5mm  
 Wire Range: 10~18AWG  
 Screw Torque: 14 lb-in  
 Withstanding: AC2000V min  
 Operating Temp: -40C to +120C

Dimensions		
Poles	L	S
2	25.0	11.0
3	36.0	22.0
4	47.0	33.0
5	58.0	44.0
6	69.0	55.0
7	80.0	66.0
8	91.0	77.0
9	102	88.0
10	113	99.0
11	124	110

RoHS compliant

Item	Name	Material	Finish
1	Insulating Body	PBT (UL94V-0)	Black
2	Terminal	Brass	Tin Plating
3	Screw	Steel, M4.0	Ni Plated

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/23/10
				Checked	Lizzy	04/23/10
				Drawn	Tina	04/23/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TA6BD10-1100-XX-BK**

Description: Terminal Block