



SPECIFICATIONS

Current Rating: 20A
 Voltage Rating: 300VAC
 Terminal Material: Brass
 Terminal Screw: Steel w/ Zinc plating
 Wire Guard: PhBz, Tin plated
 Insulation Material: Thermoplastic UI94V-0
 Wire Range: 2.5mm²/0.34-2.5mm²
 Solid Wire: 12-24
 Stranded Wire: 12-24
 Torque: 5Lb-In/0.5Nm/0.56Nm
 Screw: M3
 Wire Strip Length: 7-8mm
 Withstanding: 1.6KV/2.5KV/2.5KV
 Operating Temp: -40°C to +115°C

Series	Type	Pitch		Poles	Color
CMTB	TJX	500		XX	XX
Terminal Block	TJ=No Flange	350=3.5mm	700=7mm	02-24	BK=Black
	TJF=With	381=3.81mm	762=7.62mm		GN=Green
	Mounting Flange	500=5mm	1000=10mm		BL=Blue
		508=5.08mm	1016=10.16mm		GY=Gray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/10/09
				Checked	Lizzy	02/10/09
				Drawn	Tina	02/10/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TJF-XXX-XX-XX**

Description: 5.08mm Series with Flange