



**SPECIFICATIONS**

Voltage rating: 300 VAC  
 Current rating: 10 amps  
 Terminal material: Brass  
 Terminal plating: Tin  
 Screw material: Steel  
 Screw plating: Zinc  
 Body material: Thermoplastic, UL94V-0  
 Insulation resistance: 500 megohms min.  
 Withstanding: 2000VAC/min.  
 Wire range: 14-18AWG, stranded

Series	Type	Pitch	Poles	Color
CMTB	TS501M	XXX	XX	XX
Terminal Block	Top Screw, Modular	500=5.00mm pitch 1000=10.00mm pitch	02-26	BK=Black GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TS501M-1000-XX-XX**

Description: Terminal block, 10.00mm pitch