



SPECIFICATIONS

Voltage rating: 300 VAC
 Current rating: 10 amps
 Terminal material: Brass
 Terminal plating: Tin
 Screw material: Steel
 Screw plating: Zinc
 Body material: Thermoplastic, UL94V-0
 Insulation resistance: 1000 megohms min.
 Withstanding: 2000VAC/min.
 Wire range: 16-22AWG, stranded

Dimensions					
Pole	A	B	Pole	A	B
2	10.5	5.0	16	80.5	75.0
3	15.5	10.0	17	85.5	80.0
4	20.5	15.0	18	90.5	85.0
5	25.5	20.0	19	95.5	90.0
6	30.5	25.0	20	100.5	95.0
7	35.5	30.0	21	105.5	100.0
8	40.5	35.0	22	110.5	105.0
9	45.0	40.0	23	115.5	110.0
10	50.5	45.0	24	120.5	115.0
11	55.5	50.0	25	125.5	120.0
12	60.5	55.0	26	130.5	125.0
13	65.5	60.0			
14	70.5	65.0			
15	75.5	70.0			

Series	Type	Pitch	Poles	Color
CMTB	TS501M	XXX	XX	XX
Terminal Block	TS501M Type	500=5.00mm pitch 1000=10.00mm pitch	02-26	BK=Black GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TS501M-500-XX-XX**

Description: Terminal block, 5.00mm pitch