



SPECIFICATIONS

- Voltage rating: 300VAC
- Current rating: 10 amps
- Terminal material: Brass
- Terminal plating: Tin
- Screw material: Steel
- Screw plating: Zinc
- Body material: Thermoplastic, UL94V-0
- Insulation resistance: 500 megohms min.
- Withstanding: 2,000VAC/min.
- Wire range: 16-22AWG, stranded

| Series | Type | Pitch | Poles | Color |
|----------------|----------------|--|-------|----------------------|
| CMTB | TS502 | XXX | XX | XX |
| Terminal Block | Side Entry Top | 500=5.00mm pitch 1000=10.00mm pitch | 02-26 | BK=Black GN=Green |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | | | |
| | | | | UNIT: mm | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TS502-500-XX-XX**

Description: Terminal block, 5.00mm pitch