



SPECIFICATIONS

Voltage rating: 300VAC
 Current rating: 10 amps
 Terminal material: Brass
 Terminal plating: Tin
 Screw material: Steel
 Screw plating: Zinc
 Body material: Thermoplastic, UL94V-0
 Insulation resistance: 500 megohms min.
 Withstanding: 2,000VAC/min.
 Wire range: 14-18AWG, stranded

| Series | Type | Pitch | Poles | Color |
|----------------|----------------|--|-------|----------------------|
| CMTB | TS502M | XXX | XX | XX |
| Terminal Block | Side Entry Top | 500=5.00mm pitch 1000=10.00mm pitch | 02-26 | BK=Black GN=Green |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TS502M-1000-XX-XX**

Description: Terminal block, 10.00mm pitch