



**SPECIFICATIONS**

Rating: 10 Amperes 250 VAC  
 Terminals: Tin Plated Brass  
 Barrier Material: Thermoplastic UL94V-0, Green  
 Insulation Resistance: 500Ω min at DC 500V  
 Screws: Yellow Zinc Plated Steel  
 Screw Torque: 3.5 In-lb  
 Withstanding: AC 2000V  
 Wire Range AWG: 22-16 STR

Dimensions					
Item	A	B	Item	A	B
2	10.6	5	15	75.6	70
3	15.6	10	16	80.6	75
4	20.6	15	17	85.6	80
5	25.6	20	18	90.6	85
6	30.6	25	19	95.6	90
7	35.6	30	20	100.6	95
8	40.6	35	21	105.6	100
9	45.6	40	22	110.6	105
10	50.6	45	23	115.6	110
11	55.6	50	24	120.6	115
12	60.6	55	25	125.6	120
13	65.6	60	26	130.6	125
14	70.6	65			

Series	Type	Pitch	Poles	Color
CMTB	TS502M	XXX	XX	XX
Terminal Block	Side entry top screw modular	500=5.00mm pitch 1000=10.00mm pitch	02-26	BK=Black GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/22/08
				Checked	Lizzy	10/22/08
				Drawn	Tina	10/22/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TS502M-500-XX-GN**

Description: Euro type terminal block