



SPECIFICATIONS

- Voltage rating: 300VAC
- Current rating: 10 amps
- Terminal material: Brass
- Terminal plating: Tin
- Screw material: Steel
- Screw plating: Zinc
- Body material: Thermoplastic, UL94V-0
- Insulation resistance: 500 megohms min.
- Withstanding: 2,000VAC/min.
- Wire range: 16-22AWG, stranded

Dimensions					
Pole	A	B	Pole	A	B
2	10.6	5.0	13	65.6	60.0
3	15.6	10.0	14	70.6	65.0
4	20.6	15.0	15	75.6	70.0
5	25.6	20.0	16	80.6	75.0
6	30.6	25.0	17	85.6	80.0
7	35.6	30.0	18	90.6	85.0
8	40.6	35.0	19	95.6	90.0
9	45.6	40.0	20	100.6	95.0
10	50.6	45.0	21	105.6	100.0
11	55.6	50.0	22	110.6	115.6
12	60.6	55.0	23	115.6	110.0

Series	Type	Pitch	Poles	Color
CMTB	TS503M	XXX	XX	XX
Terminal Block	Side entry top screw modular	500=5.00mm pitch 1000=10.00mm pitch	02-26	BK=Black GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
A	DWG, TBL	09/13/11	GL	Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TS503M-500-XX-XX**

Description: Terminal block, 5.00mm pitch