



SPECIFICATIONS

Voltage rating:	250VAC
Current rating:	15 amps/way max.
Terminal body material:	Brass, machined
Terminal screw material:	Steel
Terminal screw plating:	Zinc or tin
Wire guard:	Copper alloy
Solder tail plating:	Tin
Insulator material:	Polyamide (glass filled) UL94V-0
Contact resistance:	20 milliohms max.
Insulation resistance:	5,000 megohms min./1000V
Withstanding:	1,500VAC min.
Torque:	4kgf.cm/M3
Wire range:	12-24AWG
Soldering temperature:	250°C/5 sec. max.
Operating temperature:	-33°C to +120°C

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TSA-500-XX-GN**

Description: Terminal block, 5.0mm/10.0mm pitch