


SPECIFICATIONS

- Current Rating: 8A/8/A
- Voltage Rating: 300VAC
- Terminal Body: Brass
- Terminal Screw: Steel Zinc Plating
- Wire Guard: PhBz Tin plated
- Insulator: Thermoplastic UL94V-0
- Wire Range: 1.5mm
- Solid Wire: 16-28
- Stranded Wire: 16-28
- Torque: 1.7Lb-in/0.2Nm
- Screw: M2
- Wire Strip Length: 6-7mm
- Withstanding: 1.6KV/2.5KV
- Operating Temp: -40°C to +115°C



N = Number of contacts

Series	Type	Pitch	Poles	Color
CMTB	TSX	XXX	XX	XX
Terminal Block	TSC=Front Rail TSD=Rear Rail	350(=3.50mm), 381,500,700,762,1000	02-24	BK=Black GN=Green BL=Blue GY=Gray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/10/08
				Checked	Lizzy	12/10/08
				Drawn	Tina	12/10/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-TSD-350-XX-XX**

Description: Pluggable Terminal Block 3.5mm