



Series	Height H (mm)	No. of Rows	Type	No. of Pins	Pin Length	Plating	Options
CPH	X	2	SM	XX	CS2.0	XX	XX
Pin header, 1.27mm pitch	[blank]=1.50, B=1.00, C=1.70*, D=2.00, E=2.54* *Dual row only	2= Dual rows 1= Single row	[blank]=Straight SM=Surface mount RA=Right angle	1-40 (single row) 2-80 (double row)	CS2.0=.07" (2.0mm) contact length	SGXX=Duplex GDXX=Gold XX=Flash if blank, 03, 05, 10, 15, 30µ"	[blank]=None CP=Centering pin PPL=Pick cap TR=Tape & reel TB=Tube

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/25/06
				Checked	Lizzy	08/25/06
				Drawn	Tina	08/25/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPH-2-SM-XX-CS2.0-XX-XX**  
 Description: Pin header, 1.27mm pitch, dual row, SMT type