



SPECIFICATIONS

Current rating: 1 amp
 Voltage rating: 500VAC
 Contact material: Brass
 Contact plating: Tin, or gold
 Contact resistance: 10 milliohms max.
 Insulator material: Nylon 6T, UL94V-0
 Insulator resistance: 5,000 megohms min.
 Withstanding: 500VAC for 1 min.
 Operating temperature: -40°C to +105°C

Series	Height H (mm)	Rows	Type	Positions	Pin Length	Plating	Options
CPH	X	2	XX	XX	CS3.8	XX	XX
Pin header, 1.27mm pitch	[blank]=1.50, B=1.00, C=1.70*, D=2.00, E=2.54* *Dual row only	2=Dual rows 1=Single row	[blank]=Straight SM=Surface mount RA=Right angle	1-40 (single row) 2-80 (double row)	CS=Customer specified pin length (3.8mm)	SGXX=Duplex GDXX=Gold XX=Flash if blank, 03, 05, 10, 15, 30µ"	[blank]=None CP=Centering pin PPL=Pick cap TR=Tape & reel TB=Tube

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/23/07
				Checked	Lizzy	03/23/07
				Drawn	Tina	03/23/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPH-B-2-SM(10.67)-28-CS3.8-GD**

Description: Pin header, 1.27" x 1.27" pitch, custom surface mount