



SPECIFICATIONS

Contact resistance: 30 milliohms max.  
 Insulation resistance.: 100 megohms min.  
 Withstanding: 500VAC for 1 min.

Note: ▲ = most important dimension

No.	Description	Material	Finish
1	Ground terminal	0.4T brass	Silver plate
2	Ring spring	0.25T phosphor bronze	Silver plate
3	Break terminal	0.4T brass	Silver plate
4	Break terminal	0.4T brass	Silver plate
5	Tip spring	0.25T phosphor bronze	Silver plate
6	Barrel (unthreaded)	Brass	Nickel plate
7	Housing	POM	Black
8	Cover	PC	Transparent
9	Spring	SUS-304	

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/26/06
				Checked	Lizzy	05/26/06
				Drawn	Tina	05/26/06

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPJ-01-A**

Description: 3.5ø phone jack

0.0 ± 0.35 0.00 ± 0.20 Angles ± 3'  
 UNIT: mm

