



SPECIFICATIONS

Voltage Rating: 50 VDC
 Current Rating: 1 A
 Contact resistance: 30 milliohms max.
 Insulation resistance: 100 megohms min.
 Withstanding: 500 VAC/1 min.

RoHS compliant

Series	Type	Bushing	Schematic	Ring plating	Terminal plating	Options
CPJ	6200A	MT	E	X	X	XX
Phone jack	6.3mm side entry PCB mount	Metal threaded	See table	N=Nickel (std) G=Gold O=No ring	S=Silver (std) T=Tin G=Gold	[Blank]=Kinked terminals HW=Nut and washer BL=Forked terminals SNP=Snap holder

ITEM	MATERIAL	FINISH
Housing	ABS	94HB
Earth Spring	Brass Y=0.4	MB:Cu,Ag
Tip Spring	Bronze Y=0.3	MB:Cu,Ag
Ring Terminal	Brass Y=0.4	MB:Cu,Ag
Terminal 4	Bronze Y=0.3	MB:Cu,Ag
Terminal	Brass Y=0.4	MB:Cu,Ag
Terminal	Bronze Y=0.3	MB:Cu,Ag
Terminal	Brass Y=0.4	MB:Cu,Ag
Terminal	Bronze Y=0.3	MB:Cu,Ag
Terminal	Steel T=0.5	MB:Ni
Sleeve	Brass	MB:Ni
Nut	Brass	MB:Ni
Washer	Steel T=0.5	MB:Ni

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/24/12
				Checked	Lizzy	12/24/12
				Drawn	Tina	12/24/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPJ-6200A-MT-E-X-X-HW**

Description: 6.3mm phone jack with switches, vertical PCB mount