



Item	Name	Material	Finish
1	Housing	PA66	Black
2	Sleeve shunt	0.4T Bronze	Silver plate
3	Ring spring	0.4T Phosphor bronze	Silver plate
4	Ring shunt	0.4T Bronze	Silver plate
5	Tip spring	0.4T Phosphor bronze	Silver plate
6	Tip shunt	0.4T Bronze	Silver plate
7	Washer	0.4T Brass	Nickel plate
8	Nut	2.2T Brass	Nickel plate

SPECIFICATIONS
 Contact resistance: 30 milliohms max.
 Insulation resistance: 100 megohms min. at 500VDC
 Withstanding: 500VAC for 1 min.

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPJ-636P20FS4BP0G**

Description: Phone jack, ø6.3mm