



SPECIFICATIONS
 Contact Resistance: 30mΩ max.
 Insulation Resistance: 100MΩ min. @ DC 500V
 Withstanding: AC 500V for 1 minute

Item	Name	Material	Finish
1	Housing	PA9T	Black Color
2	Earth Terminal	0.2T Phosphor Bronze	Silver Plated
3	Shunt Terminal B	0.3T Bronze	Silver Plated
4	Tip Spring	0.3T Phosphor Bronze	Silver Plated

Series	Style	Bushing	Schematic	Bushing Plating	Terminal Plating	Housing Color
CPJ	J316	P	X	E	X	XX
Phone jack	3.5mm side entry surface mount	P=Plastic bushing	See table (A-F)	E=None	S=Silver (std) T=Tin G=Gold	BK=Black RD=Red GN=Green BL=Blue GY=Gray BG=Beige

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/01/05
				Checked	Lizzy	12/01/05
				Drawn	Tina	12/01/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPJ-J316-P-X-E-X-XX**

Description: 3.5 Phone Jack