


Pin Hole Layout  
Jack Bottom View



Arrangement of Contact

ARRANGEMENT OF CONTACTS						
NO. OF CONTACTS	3	4	5	6	7	8
MODEL NO.	MDC-113 @	MDC-114 @	MDC-115 @	MDC-116 @	NOT AVAILABLE	MDC-118 @
HOLE LAYOUT						

SPECIFICATIONS

Current/voltage rating: 100VAC, 1 amp max.  
12VDC, 2 amps max.  
Contact resistance: 30 milliohms max.  
Insulation resistance: 50 megohms min.  
Withstanding: 250VAC for 1 min.  
Insertion force: 1kg - 4.5kg  
Withdrawal force: 0.9kg - 3kg

Series	Positions	Mounting
CPMD	XX	FM
Vertical low profile mini DIN socket	3, 4, 5, 6, 8	FM=Flange mount

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
					UNIT: mm	

**Central Components Manufacturing**  
440 Lincoln Blvd., Middlesex, New Jersey 08846  
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPMD-XX-FM**

Description: Mini DIN socket, 3-8 pin, straight type