


These three springs have to press down when assembly.



Series	Type	Contact
CPMDP	002	XX
Mini Din Power Plug Wire Mount Male	Type 002	2 Power 1 Data

Item	Name	Material	Finish
1	Outer Hoos	ABS	
2	Metal Sleeve	Brass	Nickel
3	Clamp	Brass	Nickel
4	Body With Pin	PBT Brass	Silver
5	Plastic Ring	POM	
6	Metal Cover	Brass	Nickel
7	Coil Spring	Steel	
8	Inner Hood	ABS	
9	Strain Relief	PVC	

**SPECIFICATIONS**  
 Rating: PIN A&B: 20V DC 7.5A Max (Pin DIA. 1.5ø)  
 PIN C: 20V DC 1A Max. (Pin DIA. 1.0ø)  
 Insulation Resistance: 50M OHM Min. at 250V DC  
 Withstanding: 250V AC/1 Minute

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/09
				Checked	Lizzy	05/15/09
				Drawn	Tina	05/15/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPMDP-002-21**

Description: Mini Din Power Plug Single Arrow