


SPECIFICATIONS

Shell material: Steel
 Terminal material: Brass
 Bushing material: Steel
 Contact resistance: 30 milliohms max.
 Insulation resistance: 100 megohms min.
 Withstanding: 500 VAC/1 min.
 Insertion force: 3 Kgf max.
 Extraction force: 0.08 Kgf min.



RoHS compliant

Item	Name	Material	Finish
1	Phone Jack Shell	0.3T Brass	Nickel Plating
2	Mounting Bracket	0.4T Iron	Tin Plating
3	Pin	0.25T Brass	Tin Plating
4	Insulator	PBT	White
5	Insulator	PBT	Black
6	Insulator	Bakelite	Black

Series	Style	Plating			Color	
CPRJ	P606	XXX			XX	
RCA jack	Straight thru-hole	Bushing N=Nickel (std) G=Gold	Terminal T=Tin (std) N=Nickel G=Gold	Shell T=Tin (std) G=Gold	BK=Black BN=Brown RD=Red OR=Orange YL=Yellow	GR=Green BL=Blue VI=Violet GY=Gray WT=White

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPRJ-P606-XXX-XX**

Description: RCA jack, straight, thru-hole PCB mount